otosp

Page

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

*

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: Fotospeed LD20 Part A

· Article number: 100144 200L

· Application of the substance / the preparation Developer for photographic use

· Manufacturer/Supplier:

Jay House LTD Unit 6B Park Lane Industrial Estate Corsham, Wiltshire SN13 9LG,United Kingdom Phone +441249 714555 www.fotospeed.com, Email: info@fotospeed.com

. Further information obtainable from: Department environment and safety.Email:info@fotospeed.com . 1.4 Emergency telephone number: +441249 714555

2 Hazards identification

· Hazard description:



Xn Harmful N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 40 Limited evidence of a carcinogenic effect.

R 41 Risk of serious damage to eyes.

R 43 May cause sensitisation by skin contact.

R 50 Very toxic to aquatic organisms.

R 68 Possible risk of irreversible effects.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· GHS label elements

Danger

H318 - Causes serious eye damage.

Warning

H341 - Suspected of causing genetic defects. H351 - Suspected of causing cancer.

Warning

H400 - Very toxic to aquatic life.

(Contd. on page 2)

⁻ GB

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Fotospe

Trade name: Fotospeed LD20 Part A

(Contd. of page 1)

	>	Warning
۰.		

- H317 May cause an allergic skin reaction.
- · Prevention:
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- · Response:
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P321 Specific treatment (see on this label).
- · Storage:
- P405 Store locked up.
- · Disposal:
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 123-31-9 EINECS: 204-617-8	1,4-dihydroxybenzene Carc. Cat. 3, Muta. Cat. 3; 🕱 Xn, 🕱 Xi, 🐱 N; R 22-40-41-43-68-50	10-25%
	Danger: $\textcircled{3.3/1}$ Warning: $\textcircled{3.5/2}, 3.6/2; \textcircled{4.1.A/1}; \textcircled{1.3.1.O/4}, 3.4.S/1$	
CAS: 50-00-0	formaldehyde	<1%
EINECS: 200-001-8	Carc. Cat. 3; 😹 T, 🚾 C; R 23/24/25-34-40-43	
	Danger: 🛞 3.1.0/3, 3.1.D/3, 3.1.I/3; 🕎 3.2/1B	
	Warning: 🚯 3.6/2; 3.4.S/1	

4 First aid measures

- · General information:
- Immediately remove any clothing/shoes soiled by the product.
- Take affected persons out into the fresh air.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

· Suitable extinguishing agents:

- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards caused by the substance, its products of combustion or resulting gases:
- Nitrogen oxides (NOx)
- Carbon monoxide (CO)
- Sulphur dioxide (SO2)

. . . .

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

(Contd. of page 2)

Trade name: Fotospeed LD20 Part A

Under certain fire conditions, traces of other toxic gases cannot be excluded. • **Protective equipment:** Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Wear protective clothing.

Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Pick up mechanically.

7 Handling and storage

· Handling:

- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: Protect from heat.

· Storage:

- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
 Store away from oxidizing agents.
 Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from exposure to the light.

Store under lock and key and out of the reach of children.

Recommended storage temperature: 5-25°C

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-31-9 1,4-dihydroxybenzene (10-25%)

WEL Long-term value: 0.5 mg/m3

50-00-0 formaldehyde (<1%)

WEL Short-term value: 2.5 mg/m3, 2 ppm

Long-term value: 2.5 mg/m³, 2 ppm

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 4)

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Fotospe

Trade name: Fotospeed LD20 Part A

(Contd. of page 3)

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated. required at the appearance from fumes/vapours/aerosol. Filter ABEK Ensure adequate ventilation

· Protection of hands:



Protective gloves

Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR Nitrile rubber, NBR Neoprene gloves

· Penetration time of glove material

Gove material: Butyl rubber with breakthroug-time: > 480 min, layer thickness: >0.4 mm

Gloves made of nitrile rubber with layer thickness >0,38mm and breakthrough-time >480min

Glove material: Neopren with breakthrough time: >240 min, layer thickness: >0,65 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

General Information		
Form:	Fluid	
Colour:	Light yellow	
Odour:	Recognizable	
Change in condition Melting point/Melting range Boiling point/Boiling range		
Flash point:	Not applicable.	
Ignition temperature:	355°C	
Self-igniting:	Product is not selfigniting.	

(Contd. on page 5)

GR

Fotospe Page 5/8

Printing date 13.04.2010 version no: 1

Revision: 13.04.2010

Trade name: Fotospeed LD20 Part A

	(Contd. of pa
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	9.2 Vol %
· Vapour pressure at 20°C:	23 hPa
· Density at 20°C:	1.26 g/cm ³
· Solubility in / Miscibility with water:	Fully miscible.
· pH-value at 20°C:	5.6
· Solvent content:	
Organic solvents:	20.3 %
Water:	35.7 %
Solids content:	44.0 %

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: Stable at environment temperature.

- · Materials to be avoided: Under certain fire conditions, traces of other toxic gases cannot be excluded.
- Dangerous reactions Reacts with acids, alkalis and oxidizing agents. Reacts with acids releasing sulphur dioxide.
- Dangerous decomposition products:
- Irritant gases/vapours
- Carbon monoxide and carbon dioxide

11 Toxicological information

- Acute toxicity:
- · LD/LC50 values relevant for classification:

123-31-9 1,4-dihydroxybenzene

Oral LD50 320 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- Irritant
- · Sensitisation May cause sensitisation by skin contact.

GB



according to 1907/2006/EC, Article 31

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Trade name: Fotospeed LD20 Part A

(Contd. of page 5)

 12 Ecological information

 • Ecotoxical effects:

 • Acquatic toxicity:

 123-31-9 1,4-dihydroxybenzene

 EC50
 48h: 0.29 mg/l (daphnia magma)

 LC50
 96h: 0.044 mg/l (Pimephales promelas)

 • Remark: Very toxic for fish

 • Additional ecological information:

 • General notes:

 Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

09 01 01* water-based developer and activator solutions

· Uncleaned packaging:

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· ADR/RID class:	9 (M6) Miscellaneous dangerous substances and articles.
· Danger code (Kemler):	: 90
· UN-Number:	3082
· Packaging group:	III
· Hazard label:	9
· Special marking:	Symbol (fish and tree)
· Description of goods:	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O. (Hydroquinone (1,4-dihydroxybenzene))
· Tunnel restriction code	
· Maritime transport IM	IDG:
· IMDG Class:	9
· IMDG Class:	9

05

according to 1907/2006/EC, Article 31 Printing date 13.04.2010 version no: 1 Revision: 13.04.2010 **Trade name: Fotospeed LD20 Part A** (Contd. of page 6) · UN Number: 3082 · Label 0 · Packaging group: Ш · EMS Number: F-A,S-F · Marine pollutant: Yes Symbol (fish and tree) · Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. · Air transport ICAO-TI and IATA-DGR: · ICAO/IATA Class: 9 · UN/ID Number: 3082 · Label 9 · Special marking: Symbol (fish and tree) · Packaging group: III · Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,4dihydroxybenzene) · UN "Model Regulation": UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful N Dangerous for the environment

- Hazard-determining components of labelling: 1,4-dihydroxybenzene
- · Risk phrases:
- 40 Limited evidence of a carcinogenic effect.
- 41 Risk of serious damage to eyes.
- 43 May cause sensitisation by skin contact.
- 50 Very toxic to aquatic organisms.
- 68 Possible risk of irreversible effects.
- · Safety phrases:

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

57 Use appropriate container to avoid environmental contamination.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

GB

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Trade name: Fotospeed LD20 Part A

22	nt R-phrases	
22		
23/24/25	Harmful if swallowed.	
	5 Toxic by inhalation, in contact with skin and if swallowed.	
34	Causes burns.	
40	Limited evidence of a carcinogenic effect.	
41	Risk of serious damage to eyes.	
43	May cause sensitisation by skin contact.	
50	Very toxic to aquatic organisms.	
68	Possible risk of irreversible effects.	
RID: Règl Internation IMDG: Int IATA: Inte IATA-DGI ICAO: Inte ICAO: Inte ICAO-TI: GHS: Glob LC50: Let	of Dangerous Goods by Road) lement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations nal Transport of Dangerous Goods by Rail) ternational Maritime Code for Dangerous Goods ernational Air Transport Association R: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ernational Civil Aviation Organization Technical Instructions by the "International Civil Aviation Organization" (ICAO) bally Harmonized System of Classification and Labelling of Chemicals hal concentration, 50 percent thal dose, 50 percent	Concerning th
	compared to the previous version altered.	

Fotospe Page 1/7

according to 1907/2006/EC, Article 31

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: Fotospeed LD20 Part B
- · Article number: 100145 200L
- · Application of the substance / the preparation Developer for photographic use
- · Manufacturer/Supplier:

Jay House LTD Unit 6B Park Lane Industrial Estate Corsham, Wiltshire SN13 9LG,United Kingdom Phone +441249 714555 www.fotospeed.com, Email: info@fotospeed.com

. Further information obtainable from: Department environment and safety.Email:info@fotospeed.com

. 1.4 Emergency telephone number: +441249 714555

2 Hazards identification

· Hazard description:



Xi Irritant

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 36/38 Irritating to eyes and skin.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· GHS label elements



H314 - Causes severe skin burns and eye damage.

- · Prevention:
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- · Response:

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

P310 • Storage:

P405 Store locked up.

· Disposal:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

according to 1907/2006/EC, Article 31

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Fotospe

Trade name: Fotospeed LD20 Part B

(Contd. of page 1)

Page 2/7

3 Composition/information on ingredients

· Chemical characterization

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 584-08-7	potassium carbonate	10-25%	
EINECS: 209-529-3	🗙 Xi; R 36/38		
	Warning: 1.2/2, 3.3/2		
CAS: 497-19-8	Sodium carbonate	1-5%	
EINECS: 207-838-8			
	Warning: 13.3/2		
CAS: 1332-77-0	dipotassium tetraborate	<2%	
EINECS: 215-575-5			
	Warning: 🚸 3.7/2		
CAS: 1310-58-3	potassium hydroxide	<2%	
EINECS: 215-181-3			
	Danger: \bigcirc 3.2/1A		
	Warning: 1.0/4	1.000	
CAS: 140-01-2 EINECS: 205-391-3	Sodium diethylene triamine pentaacetic aicd (DTPA-Na5)	<2%	
	Warning: 1 3.3/2		

4 First aid measures

· General information:

- Immediately remove any clothing/shoes soiled by the product.
- Take affected persons out into the fresh air.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

• Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 \cdot Special hazards caused by the substance, its products of combustion or resulting gases:

- Nitrogen oxides (NOx)
- Carbon monoxide (CO)

Sulphur dioxide (SO2)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· Protective equipment: Do not inhale explosion gases or combustion gases.



version no: 1

Revision: 13.04.2010

at a start water

Printing date 13.04.2010

Trade name: Fotospeed LD20 Part B

(Contd. of page 2)

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Wear protective clothing.
- Measures for environmental protection: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.

7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: Protect from heat.
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Store away from oxidizing agents.
- · Further information about storage conditions:
- Keep container tightly sealed.
- Protect from heat and direct sunlight.
- Protect from exposure to the light.
- Store under lock and key and out of the reach of children.
- Recommended storage temperature: 5-25°C

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

- 1310-58-3 potassium hydroxide (<2%)
- WEL Short-term value: 2 mg/m3
- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- · Respiratory protection: Ensure adequate ventilation
- Protection of hands:



Protective gloves

Impervious gloves



Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Trade name: Fotospeed LD20 Part B

(Contd. of page 3) The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Butyl rubber, BR Nitrile rubber, NBR Neoprene gloves · Penetration time of glove material Gove material: Butyl rubber with breakthroug-time: \geq 480 min, layer thickness: \geq 0,4 mm Gloves made of nitrile rubber with layer thickness >0,38mm and breakthrough-time >480min Glove material: Neopren with breakthrough time: >240 min, layer thickness: >0,65 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles · Body protection: Protective work clothing 9 Physical and chemical properties

 General Information 		
Form:	Fluid	
Colour:	Light yellow	
Odour:	Recognizable	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. > 100°C	
· Flash point:	Not applicable.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Vapour pressure at 20°C:	23 hPa	
· Density at 20°C:	1.33 g/cm ³	
 Solubility in / Miscibility with water: 	Fully miscible.	
· pH-value at 20°C:	>13	
· Solvent content:		
Organic solvents:	0.0 %	
Water:	60.5 %	
VOC (EC)	0.00 %	

GB

Fotospe

according to 1907/2006/EC, Article 31

Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

Trade name: Fotospeed LD20 Part B

(Contd. of page 4)

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: Stable at environment temperature.
- · Materials to be avoided: Under certain fire conditions, traces of other toxic gases cannot be excluded.
- · Dangerous reactions
- Reacts with acids, alkalis and oxidizing agents.
- Reacts with acids releasing sulphur dioxide.
- · Dangerous decomposition products:
- Irritant gases/vapours
- Carbon monoxide and carbon dioxide

11 Toxicological information

· Acute toxicity:

- · LD/LC50 values relevant for classification:
- 1310-58-3 potassium hydroxide
- Oral LD50 273 mg/kg (rat)
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

- · Ecotoxical effects:
- · Acquatic toxicity:
- 1310-58-3 potassium hydroxide
- EC50 48h: 660 mg/l (daphnia magma)
- LC50 96h: 80 mg/l (fish)
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 09 01 01* water-based developer and activator solutions
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

GB

Fotospe

Page 6/7

Safety Data Sheet

according to 1907/2006/EC, Article 31



15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 7)

GB



Printing date 13.04.2010

version no: 1

Revision: 13.04.2010

(Contd. of page 6)

Trade name: Fotospeed LD20 Part B

· Code letter and hazard designation of product:



Xi Irritant

- **Risk phrases:** 36/38 Irritating to eyes and skin.
- · Safety phrases:

60 This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 22 Harmful if swallowed.
- 35 Causes severe burns.
- 36 Irritating to eyes.
- 36/38 Irritating to eyes and skin.
- 62 Possible risk of impaired fertility.
- 63 Possible risk of harm to the unborn child.
- · Department issuing MSDS: Department product safety
- · Contact: e-mail: sida@tetenal.com
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- * * Data compared to the previous version altered.