

MATERIAL SAFETY DATA SHEET

20000879/F/USA  
Approval Date: 10/12/2003  
Print Date: 10/17/2006  
Page: 1/5



-----  
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: KODAK PHOTO-FLO 200 Solution

Catalog Number(s):       146 4502 - 4 fluid ounce(s)  
                              146 4510 - 16 fluid ounce(s)

Manufacturer/Supplier: EASTMAN KODAK COMPANY, Rochester, New York 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151

For other information or to request an MSDS, call (800) 242-2424.

Synonym(s):     KAN 354804; PCD 3107; F-0107.000

-----  
2. COMPOSITION/INFORMATION ON INGREDIENTS

Weight % - Component - (CAS Registry No.)

60-70     Water (007732-18-5)  
25-30     Propylene glycol (000057-55-6)  
5-10      p-tert-octylphenoxy polyethoxyethyl alcohol (009002-93-1)

-----  
3. HAZARDS IDENTIFICATION

CONTAINS: P-tert-octylphenoxy polyethoxyethyl alcohol (009002-93-1)

WARNING!

CAUSES EYE IRRITATION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION

HMIS Hazard Ratings:

Health - 2, Flammability - 1, Reactivity - 0, Personal Protection - A

NFPA Hazard Ratings:

Health - 1, Flammability - 1, Reactivity (Stability) - 0

NOTE: HMIS and NFPA hazard indexes involve data review and interpretation that may vary among companies. They are intended only for rapid, general identification of the magnitude of the potential hazards. The personal protection index is only intended for general guidance on personal protection equipment (PPE) that is suitable for the potential hazards of the material. PPE (e.g., respirators) may not be needed if engineering controls (e.g., local ventilation) are adequate. An asterisk (\*), in the HMIS health field, designates potential chronic or target organ hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

-----  
4. FIRST-AID MEASURES

Inhalation: If symptomatic, move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.

Eyes: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

Skin: Wash with soap and water. Get medical attention if symptoms occur.

MATERIAL SAFETY DATA SHEET

200000879/F/USA  
Approval Date: 10/12/2003  
Print Date: 10/17/2006  
Page: 2/5

-----  
Ingestion: Drink 1-2 glasses of water. Seek medical attention. Never give anything by mouth to an unconscious person.

-----  
5. FIRE FIGHTING MEASURES

Extinguishing Media: Water spray, carbon dioxide (CO2), dry chemical, alcohol foam

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide

Unusual Fire and Explosion Hazards: None

-----  
6. ACCIDENTAL RELEASE MEASURES

Flush to sewer with large amounts of water.

-----  
7. HANDLING AND STORAGE

Personal Precautionary Measures: Avoid contact with eyes and prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials.

Storage: Keep container closed.

-----  
8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: Not established

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions.

Respiratory Protection: None should be needed.

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin Protection: It is a good industrial hygiene practice to minimize skin contact. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Recommended Decontamination Facilities: Eye bath, washing facilities, safety shower

-----  
9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Liquid

Color: Colorless

Odor: Odorless

Specific Gravity (water = 1): 1.028

Vapor Pressure at 20°C (68°F): 24 mbar (18 mm Hg)

MATERIAL SAFETY DATA SHEET

200000879/F/USA  
Approval Date: 10/12/2003  
Print Date: 10/17/2006  
Page: 3/5

-----  
Vapor Density (Air = 1): 0.6  
Volatile Fraction by Weight: 60-70 %  
Boiling Point: >100°C (>212°F)  
Solubility in Water: Complete  
pH: 7.0  
Flash Point: None

-----  
10. STABILITY AND REACTIVITY

Stability: Stable  
Incompatibility: Strong oxidizing agents  
Hazardous Polymerization: Will not occur.

-----  
11. TOXICOLOGICAL INFORMATION

Effects of Exposure:

Inhalation: Expected to be a low hazard for recommended handling.  
Eyes: Causes irritation.  
Skin: Prolonged or repeated skin contact may cause irritation.  
Ingestion: Expected to be a low ingestion hazard.

Acute Toxicity Data:

Oral LD-50 (rat): 5000 mg/kg  
Skin irritation: slight irritation  
Eye irritation: moderate irritation

-----  
12. ECOLOGICAL INFORMATION

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity

Fish LC50 mg/l:	10-100
Daphnid EC50 mg/l:	Not available
Algal IC50 mg/l:	Not available
Organics Readily Degradable (>70%):	Yes (7 days)
Potential Bioaccumulation:	Log Pow <1
COD (approximate g/l):	201
BOD5 (approximate g/l):	377
Potential Toxicity Waste treatment microorganisms EC50 (mg/l):	Not available

-----

MATERIAL SAFETY DATA SHEET

200000879/F/USA  
Approval Date: 10/12/2003  
Print Date: 10/17/2006  
Page: 4/5

-----  
13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Flush to sewer with large amounts of water.

-----  
14. TRANSPORT INFORMATION

For transportation information regarding this product call the Kodak Worldwide Transportation Hazmat Hot Line: (585) 722-2400 between 8 a.m. and 5 p.m. (Eastern Standard Time), Monday through Friday.

-----  
15. REGULATORY INFORMATION

- Material(s) known to the State of California to cause cancer: None
- Material(s) known to the State of California to cause adverse reproductive effects: None
  
- Carcinogenicity Classification (components present at 0.1% or more):
  - International Agency for Research on Cancer (IARC): None
  - American Conference of Governmental Industrial Hygienists (ACGIH): None
  - National Toxicology Program (NTP): None
  - Occupational Safety and Health Administration (OSHA): None
  
- Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: None

-----  
16. OTHER INFORMATION

US/Canadian Label Statements:

CONTAINS: P-tert-octylphenoxy polyethoxyethyl alcohol (009002-93-1)

WARNING!

CAUSES EYE IRRITATION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION

Avoid contact with eyes and prolonged or repeated contact with skin.

Use with adequate ventilation.

Wash thoroughly after handling.

FIRST AID: In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Keep out of reach of children.

For additional information, see Material Safety Data Sheet (MSDS) for this material.

-----  
The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

MATERIAL SAFETY DATA SHEET

200000879/F/USA

Approval Date: 10/12/2003

Print Date: 10/17/2006

Page: 5/5

-----

-----

R-1, S-2, F-1, C-0