

SAFETY DATA SHEET

1. Identification

Product identifier	Battery Cleaner
Other means of identification	
Product code	03176
Recommended use	Battery cleaner
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/	Distributor information
Manufacturer	
Company name	CRC Industries, Inc.
Address	885 Louis Dr.
	Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical	800-521-3168
Assistance	
Customer Service	800-272-4620
24-Hour Emergency	800-424-9300 (US)
(CHEMTREC)	703-527-3887 (International)
Website	www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Gases under pressure	Liquefied gas	
Health hazards	Not classified.		
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			



Signal word	Warning
Hazard statement	Contains gas under pressure; may explode if heated.
Precautionary statement	
Prevention	Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying.
Response	Wash hands after handling.
Storage	Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Water		7732-18-5	80 - 90	
Liquefied Petroleum Gas		68476-86-8	5 - 10	
2-Butoxyethanol		111-76-2	1 - 3	

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a POISON CENTER or doctor/physician.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not get this material in contact with skin. Avoid prolonged exposure. Wear appropriate personal protective equipment. Use only in well-ventilated areas. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

ccupational exposure limi US. OSHA Table Z-1 Lin	nits for Air Contamin	-	CFR 1910.10		
Components	Т	уре		<u> </u>	/alue
2-Butoxyethanol (CAS 111-76-2)	F	EL			240 mg/m3
				5	50 ppm
US. ACGIH Threshold L Components		уре		١	/alue
2-Butoxyethanol (CAS 111-76-2)	Т	WA		2	20 ppm
US. NIOSH: Pocket Gui	de to Chemical Hazar	ds			
Components	т	уре		۱	/alue
2-Butoxyethanol (CAS 111-76-2)	Т	WA		2	24 mg/m3
				5	5 ppm
iological limit values					
ACGIH Biological Expo Components	sure Indices Value	Det	erminant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	acid	oxyacetic I (BAA), I hydrolysis	Creatinine i urine	n *
* - For sampling details, p	blease see the source				
xposure guidelines					
US - California OELs: S	kin designation				
2-Butoxyethanol (CA US - Minnesota Haz Sul		applies	Can b	e absorbed thro	bugh the skin.
2-Butoxyethanol (CA US - Tennesse OELs: S			Skin d	esignation appl	lies.
2-Butoxyethanol (CA US NIOSH Pocket Guide		s: Skin d		e absorbed thro	bugh the skin.
2-Butoxyethanol (CA US. OSHA Table Z-1 Lin		ants (29 (e absorbed thro 00)	bugh the skin.
2-Butoxyethanol (CA	S 111-76-2)		Can b	e absorbed thro	ough the skin.
ppropriate engineering ontrols	should be matcl or other engine	ned to cor ering cont	nditions. If ap rols to mainta	plicable, use p ain airborne lev	r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatior rels below recommended exposure limits. If airborne levels to an acceptable level.
dividual protection measu	ires, such as persona	I protect	ive equipme	nt	
Eye/face protection	Wear safety gla	sses with	side shields	(or goggles).	
Skin protection					
Hand protection	Wear protective	gloves su	uch as nitrile.		
Other	Wear appropria			-	
Respiratory protection	In case of insuff determine actua				atory equipment. Air monitoring is needed
Thermal hazards	Wear appropria		-	-	-
	When using do	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Clear.
Odor	Odorless.
Odor threshold	Not available.
рН	8.5
Melting point/freezing point	-103 °F (-75 °C) estimated

Material name: Battery Cleaner

Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	None (Closed Cup)
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	10.6 % estimated
Vapor pressure	268.5 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	1.04
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	446 °F (230 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	94.2 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of e	exposure
Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxicological effe	ects

Acute toxicity	Not available.		
Product Species		Test Results	
Battery Cleaner			
Acute			
Dermal			
LD50	Rabbit	7723.0923 mg/kg estimated	
Inhalation			
LC50	Rat	15797.2334 mg/l, 4 hours estimated	
		15797.2334 ppm, 4 hours estimated	
Oral			
LD50	Rat	16499.332 mg/kg estimated	

Product	Species	Test Results	
Chronic			
Inhalation			
LC50	Rat	83.1988 mg/l estimated	
* Estimates for product may b	e based on additional compon	ent data not shown.	
Skin corrosion/irritation	Prolonged skin contact may	cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall	Evaluation of Carcinogenicit	V	
2-Butoxyethanol (CAS 11	1-76-2)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not available.		
Chronic effects	Prolonged inhalation may be	harmful. May be harmful if absorbed through skin.	
		sorbed through the skin in toxic amounts if contact is repeated and ve not been observed in humans.	

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Product		Species	Test Results	
Battery Cleaner				
Acute				
Crustacea	EC50	Daphnia	54412.6953 mg/l, 48 hours estimated	
Fish	LC50	Fish	53543.8477 mg/l, 96 hours estimated	
Components		Species	Test Results	
2-Butoxyethanol (CAS 111-7	76-2)			
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	1550 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours	
* Estimates for product may	be based on	additional component data not shown.		
Persistence and degradability	No data is	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.			
Partition coefficient n-octa 2-Butoxyethanol	nol / water (log Kow) 0.81, log Pow		
Mobility in soil	No data a	No data available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	ons			
Disposal of waste from residues / unused products	The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Hazardous waste code	Not regula	Not regulated.		

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, limited quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, limited quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
· · ·	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US federal regulations

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-Butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

	Safe Drinking Water Act (SDWA)	Not regulated.		
I	Food and Drug Administration (FDA)	Not regulated.		
		I Reauthorization Act of 1986 Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No	(SARA)	
	SARA 302 Extremely hazardous substance	No		
US s	tate regulations			
I	US. New Jersey RTK - Subst	ances: Listed substance		
ı	2-Butoxyethanol (CAS 11 US. Massachusetts RTK - Su			
I	2-Butoxyethanol (CAS 11 US. Pennsylvania RTK - Haz	,		
	2-Butoxyethanol (CAS 11			
I	US. Rhode Island RTK	,		
	2-Butoxyethanol (CAS 11	1-76-2)		
I	US. California Proposition 6 WARNING: This product or reproductive harm.		ne State of California to cause cancer and I	birth defects or other
	US - California Propositi	ion 65 - CRT: Listed date/Car	cinogenic substance	
	1,4-Dioxane (CAS 12 Ethylene oxide (CAS	3-91-1)	Listed: January 1, 1988 Listed: July 1, 1987	
	Ethylene oxide (CAS		Listed: August 7, 2009	
		ion 65 - CRT: Listed date/Fem		
	Ethylene oxide (CAS		Listed: February 27, 1987	
	Ethylene oxide (CAS	75-21-8)	Listed: August 7, 2009	
	tile organic compounds (VO EPA	C) regulations		
	VOC content (40 CFR 51.100(s))	7.9 %		
	Consumer products (40 CFR 59, Subpt. C)	Not regulated		
:	State			
	Consumer products	Not regulated		
Inter	national Inventories			
(Country(s) or region	Inventory name		On inventory (yes/no)*
	Australia	Australian Inventory of Chemi	cal Substances (AICS)	Yes
(Canada	Domestic Substances List (D	SL)	Yes
(Canada	Non-Domestic Substances Lis	st (NDSL)	No
(China	Inventory of Existing Chemica	I Substances in China (IECSC)	Yes
I	Europe	European Inventory of Existin Substances (EINECS)	g Commercial Chemical	No
I	Europe	European List of Notified Che	mical Substances (ELINCS)	No
	Japan	Inventory of Existing and New	Chemical Substances (ENCS)	No
I	Korea	Existing Chemicals List (ECL)		Yes
I	New Zealand	New Zealand Inventory		Yes
I	Philippines	Philippine Inventory of Chemi (PICCS)	cals and Chemical Substances	Yes
	United States & Puerto Rico	Toxic Substances Control Act ents of this product comply with the	(TSCA) Inventory e inventory requirements administered by the go	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	09-18-2013
Prepared by	Allison Cho
Version #	01
Further information	CRC# 530B
HMIS® ratings	Health: 1* Flammability: 0 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 0 Instability: 0
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.