



Material Safety Data Sheet

Date of Preparation: October 28, 2005

Section 1 - Product Information

Product Name: AUTOBODY FILLER REPAIR KIT
Product Code: 310, 310C, 310T, 312, 312C, 312K, 316C
Emergency Phone: Chemtrec 800-424-9300
Company: Bondo Corporation
3700 Atlanta Industrial Parkway NW
Atlanta, GA 30331
Revision Number: 1
Intended Use: Autobody repair

This product is packaged with Red Cream Hardener (see the MSDS for Red Cream Hardener, Stock Number: 913).

Emergency Overview

Signs of Overexposure: Irritability, Intestinal upset (nausea, vomiting, diarrhea), Irritation of nose, throat, and airways, central nervous system effects (dizziness, drowsiness, weakness, fatigue, headache, unconsciousness), Loss of coordination, Mental confusion, liver damage,

Emergency First Aid: Flush eyes with plenty of water. Avoid rubbing eyes. If irritation develops, seek medical attention. Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Contact physician for advise about whether to induce vomiting. Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. Get medical attention immediately Wash with soap and water. If symptoms persist, get medical attention.

Handling: No special handling instructions.

Material Physical Appearance: Gray Paste

Fire Fighting: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Your local fire department may require that you display the NFPA 704 diamond symbol on the front and/or rear entrance to your building.

NFPA 704: Health: 2, Fire: 3, Reactivity: 0

Bondo Corporation has no oversight with respect to the guidance practices or policies or manufacturing processes of other companies handling or using this material. The information given in this MSDS is only related to the product as shipped in its original condition. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by regulations.

Section 2 - Hazardous Ingredients

Chemical Name	%	CAS#	OSHA Exposure Limits
Proprietary Resin	30.0 - 40.0	Proprietary	No PEL established
Talc	20.0 - 30.0	14807-96-6	20 mppcf
Styrene	10.0 - 20.0	100-42-5	100 ppm TWA; C 200 ppm C 200 ppm
Magnesium carbonate	10.0 - 20.0	546-93-0	total dust: 15 mg/m ³ TWA; respirable fraction: 5 mg/m ³ TWA
sodium metaborate	5.0 - 10.0	7775-19-1	No PEL established

Section 3 – Hazards Identification

Routes of Entry: Inhalation, Eye contact, Skin contact, Ingestion,

Target Organs Potentially Affected by Exposure: Eyes, Respiratory Tract, Skin, Liver, Nervous System,

Chemical Interactions That Change Toxicity: No chemical interaction known to affect toxicity.,

Medical Conditions Aggravated by Exposure: Respiratory disease including asthma and bronchitis, Eye disease, Skin disease including eczema and sensitization, Liver disease,

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Can cause mechanical irritation if dusts are generated. Causes respiratory tract irritation

Inhalation Toxicity: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes nose and throat irritation. Non-Toxic. Not known to cause systemic damage.

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause skin irritation.

Skin Absorption: No absorption hazard in normal industrial use. Component(s) may be absorbed through intact skin, but it is unlikely that harmful effects will occur unless contact is prolonged, repeated, and extensive.

Eye contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Can cause slight irritation. Can cause irritation.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. Harmful if swallowed.

Ingestion Toxicity: slightly toxic

Long-Term (Chronic) Health Effects

Carcinogenicity: Contains a substance that is a possible cancer hazard based on high dose animal studies and/or a human study. .

Reproductive and Developmental Toxicity: Contains a substance(s) that is a possible reproductive system hazard based on high dose tests with laboratory animals.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Ingestion: slightly toxic

Section 4 – First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this MSDS. If swallowed, do not induce vomiting. Get medical attention immediately.

Notes to Doctor: No additional first aid information available

Section 5 – Fire Fighting Measures

Flammability Summary: Flammable

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, Hydrocarbons,

Flash Point (SFCC): 27 deg. C 80 deg. F

Lower Flammable/Explosive Limit: Not determined

Section 6 - Accidental Release

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Section 7 – Handling and Storage

Handling Technical Measures and Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment.

Storage Technical Measures and Conditions: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition.

Section 8 – Exposure Controls/Personal Protection

Engineering Measures: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Good general room ventilation should be sufficient to control airborne contaminants to safe levels.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Wear a NIOSH approved respirator if levels above the exposure limits are possible.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

Gloves: Required for prolonged or repeated contact. Use solvent resistant gloves. Barrier creams are not substitutes for full physical protection. Refer to safety equipment supplier for effective glove recommendations.

Control Parameters:

Chemical Name	ACGIH TLV-TWA	ACGIH STEL	IDLH
Proprietary Resin	Not established	Not established	Not determined
Talc	2 mg/m ³ TWA (this TLV is for the respirable fraction of dust for Talc)	Not established	Not determined
Styrene	20 ppm TWA; 85 mg/m ³ TWA	40 ppm STEL; 170 mg/m ³ STEL	Not determined
Magnesium carbonate	10 mg/m ³ TWA (The value is for total dust containing no asbestos and < 1%)	Not established	Not determined
sodium metaborate	Not established	Not established	Not determined

Section 9 – Physical and Chemical Properties

Physical State: Paste

Color: Gray

Odor: Strong Solvent

pH: Not determined

Solubility in Water: Not determined

Volatiles, % by weight: 17.82

Volatiles, % by volume: 22.47

Volatile Organic Compounds excluding exempt solvents and water:

1.69 Lb/gallon 203.01 g/l

Volatile Organic Compounds including exempt solvents and water:

1.69 LB/gallon 203.01 g/l

Vapor Density: 3.6000000

Vapor Pressure: Not determined

Boiling Point: 145.0000000 deg. C; 293 deg. F

Specific Gravity: 2.75

Weight per Gallon: 9.5126

Section 10 – Stability and Reactivity

Stability: Stable under normal conditions. May become unstable at elevated temperatures and/or pressure.

Stable Stable. However, may decompose if heated

Conditions to Avoid: Sparks, open flame, other ignition sources, and elevated temperatures.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents, Peroxides, Strong acids,

Hazardous Decomposition Products: Hydrocarbons, Carbon monoxide, Carbon dioxide,

Section 11 - Toxicological Information

Sensitization (effects of repeated exposure): No data

Component Toxicology Data (NIOSH)

Chemical Name	CAS Number	LD50/LC50
Proprietary Resin	Proprietary	No Data Available
Talc	14807-96-6	No Data Available
Styrene	100-42-5	Inhalation LC50 Rat : 12 gm/m ³ /4H; Inhalation LC50 Mouse : 9500 mg/m ³ /4H; Oral
Magnesium carbonate	546-93-0	No Data Available
sodium metaborate	7775-19-1	No Data Available

Section 12 - Ecological Information

Overview:

Avoid runoff into ground, storm drains or sewers that lead into waterways. Water runoff may cause environmental damage. There are extensive ecological data available on the various components of these products. An adequate representation of all these data is beyond the scope of this document. Please contact the information phone number found in Section 16.

Section 13 – Disposal Information

Waste Description for Spent Product: Spent or discarded material is a hazardous waste.

Disposal Methods: Dispose of in accordance with federal, state or provincial and local pollution requirements. Clean preferably with a detergent, avoid the use of solvents. This information applies only to the material as manufactured; processing, use or contamination may make this information inappropriate, inaccurate or incomplete. The generator of the waste has the responsibility for proper waste classification, transportation and disposal.

Waste Disposal Codes: D001

Section 14 – Transportation Information

DOT Basic Description:	DOT: CONSUMER COMMODITY, ORM-D IMDG: Polyester Resin Kit, 3, UN 3269, III, LTD QTY, Flash Point 27C, EmS F-E, S-D
Hazard Class:	ORM-D
UN Number:	Not Applicable
Packing Group:	Not Applicable

Section 15 - Regulatory Information

Note: Materials listed in this section may be present as trace level contaminants to raw materials. Check Section 2 - Hazardous Ingredients to determine if a significant amount is present

OSHA: This product is considered hazardous under the Federal OSHA Hazard Communication Standard.

WHMIS: B2, D2A, D2B,

SARA Title III:

Section 302 Extremely Hazardous Substances: None

Section 311 / 312 Hazard Categories: Immediate health, delayed health, fire hazard.

Section 313 Toxic Chemicals: Styrene,

You may be required to submit this MSDS to state and local emergency response agencies (SERC & LEPC) and to your local fire department. Also, you may be affected by other sections of this law, depending on the chemicals and amounts that you inventory at your location. To learn more about your responsibilities, call the EPA Hotline (800) 535-0202

TSCA status: All components in this product are on the TSCA Inventory.

Canadian Domestic Substances List: The components of this product ARE listed on the Canadian Domestic Substances List.

Proposition 65: WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

Section 16 - Preparation Information

Prepared by Bondo Corporation

Information phone number: (404) 696-2730

Do not handle until the manufacturer's safety precautions have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all products with which they come in contact.

While Bondo Corporation believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Bondo Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state or provincial and local laws and regulations.



Material Safety Data Sheet

Date of Preparation: June 7, 2006

Section 1 - Product Information

Product Name: RED CREAM HARDENER

Product Code: 4, 304, 307, 913, 913C, 928, 9301, 9307, 9307R

Emergency Phone: Chemtrec 800-424-9300

Company: Bondo Corporation
3700 Atlanta Industrial Parkway NW
Atlanta, GA 30331

Revision Number: 10

Intended Use: Curing agent.

Emergency Overview

Signs of Overexposure: Mild irritation.

Irritation of nose, throat, and airways,

Emergency First Aid: Flush eyes for 20 minutes. Get immediate medical attention. Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Contact physician for advise about whether to induce vomiting. Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. Get medical attention immediately Wash with soap and water. If symptoms persist, get medical attention.

Handling: Avoid unnecessary exposure.

Material Physical Appearance: Red Paste

Fire Fighting: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid.

Your local fire department may require that you display the NFPA 704 diamond symbol on the front and/or rear entrance to your building.

NFPA 704: Health: 1, Fire: 1, Reactivity: 0

Bondo Corporation has no oversight with respect to the guidance practices or policies or manufacturing processes of other companies handling or using this material. The information given in this MSDS is only related to the product as shipped in its original condition. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by regulations.

Section 2 - Hazardous Ingredients

Chemical Name	%	CAS#	OSHA Exposure Limits
Benzoyl Peroxide	40.0 - 50.0	94-36-0	No PEL established
water	10.0 - 20.0	7732-18-5	No PEL established
C9-11-branched alkyl benzoate	10.0 - 20.0	131298-44-7	No PEL established
Zinc stearate	1.0 - 5.0	557-05-1	total dust: 15 mg/m ³ TWA; respirable fraction: 5 mg/m ³ TWA

Section 3 – Hazards Identification

Routes of Entry: Skin contact, Eye contact, Ingestion, Inhalation, Skin contact, Eye contact,

Target Organs Potentially Affected by Exposure: Skin, Nervous System, Urinary Tract, Respiratory Tract,

Chemical Interactions That Change Toxicity: None Known,

Medical Conditions Aggravated by Exposure: Skin disease including eczema and sensitization, Respiratory disease including asthma and bronchitis,

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation: Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

Inhalation Toxicity: Non-Toxic. Not known to cause systemic damage.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: Minimal hazard in normal industrial use. May cause gastrointestinal discomfort

Eye contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. No hazard in normal industrial use. Can cause mechanical irritation if dusts are generated.

Ingestion Irritation: Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects

Carcinogenicity: None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. ,

Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: Upon prolonged or repeated exposure, minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

Ingestion: Harmful if swallowed. May cause systemic poisoning.

Section 4 – First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion: Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute.

Notes to Doctor: No additional first aid information available

Section 5 – Fire Fighting Measures

Flammability Summary: Combustible at elevated temperatures

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid.

Fire and/or Explosion Hazards: Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire. Dusts at sufficient concentrations can form explosive mixtures with air.

Use process enclosures to control the level of dust in the air.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, Formaldehyde, Hydrocarbons,

Flash Point (SFCC): 277 deg. C 531 deg. F

Lower Flammable/Explosive Limit: Not determined

Section 6 - Accidental Release

Personal Precautions and Equipment: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS

Methods for Clean-up: No special spill clean-up considerations. Collect and discard in regular trash.

Section 7 – Handling and Storage

Handling Technical Measures and Precautions: Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Wash thoroughly after handling.

Storage Technical Measures and Conditions: Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use.

Section 8 – Exposure Controls/Personal Protection

Engineering Measures: Local exhaust ventilation, process enclosures, or other engineering controls are imperative when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Respiratory Protection: Use NIOSH approved respirator for particulate when handling dried material. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Respiratory protection may be required in addition to ventilation depending upon conditions of use.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

An eye wash station must be available where this product is used. Wear goggles if dusts can reach the exposure limit.

Skin Protection: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where use can result in skin contact, practice good personal hygiene.

Gloves: Required for prolonged or repeated contact. Use solvent resistant gloves. Barrier creams are not substitutes for full physical protection. Refer to safety equipment supplier for effective glove recommendations.

Control Parameters:

Chemical Name	ACGIH TLV-TWA	ACGIH STEL	IDLH
Benzoyl Peroxide	Not established	Not established	Not determined

water	Not established	Not established	Not determined
C9-11-branched alkyl benzoate	Not established	Not established	Not determined
Zinc stearate	Not established	Not established	Not determined

Section 9 – Physical and Chemical Properties

Physical State: Paste

Color: Red

Odor: None

pH: Not determined

Solubility in Water: Not determined

Volatiles, % by weight: 20.00

Volatiles, % by volume: 24.00

Volatile Organic Compounds excluding exempt solvents and water:

0.00 Lb/gallon 0.00 g/l

Volatile Organic Compounds including exempt solvents and water:

0.00 LB/gallon 0.00 g/l

Vapor Density: Not determined

Vapor Pressure: Not determined

Boiling Point: Not determined

Specific Gravity: 1.33

Weight per Gallon: 8.346

Section 10 – Stability and Reactivity

Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Contamination

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents,

Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide, Formaldehyde, Hydrocarbons,

Section 11 - Toxicological Information

Sensitization (effects of repeated exposure): No data

Component Toxicology Data (NIOSH)

Chemical Name	CAS Number	LD50/LC50
Benzoyl Peroxide	94-36-0	7710
water	7732-18-5	No data available
C9-11-branched alkyl benzoate	131298-44-7	No data available
Zinc stearate	557-05-1	Oral LD50 Rat : >10 gm/kg; Oral LD50 Mouse : >10 gm/kg

Section 12 - Ecological Information

Overview:

Avoid runoff into ground, storm drains or sewers that lead into waterways. Water runoff may cause environmental damage. There are extensive ecological data available on the various components of these products. An adequate representation of all these data is beyond the scope of this document. Please contact the information phone number found in Section 16.

Section 13 – Disposal Information

Waste Description for Spent Product: Spent or discarded material is non-hazardous according to environmental regulations.

Disposal Methods: Dispose of in accordance with federal, state or provincial and local pollution requirements. Clean preferably with a detergent, avoid the use of solvents. This information applies only to the material as manufactured; processing, use or contamination may make this information inappropriate, inaccurate or incomplete. The generator of the waste has the responsibility for proper waste classification, transportation and disposal.

Waste Disposal Codes:

Section 14 – Transportation Information

DOT Basic Description:	For 304, 307, 913, 913C, 928: DOT: Consumer Commodity, ORM-D IMDG: Organic Peroxide Type E, Solid (Dibenzoyl Peroxide Paste, 50%), 5.2, UN 3108, II, LTD QTY, EmS F-J, S-R
	For 9301, 9307 and 9307R Organic Peroxide Type E, Solid (Dibenzoyl Peroxide Paste, 50%), 5.2, UN 3108, II, EmS F-J, S-R
Hazard Class:	ORM-D
UN Number:	N/A
Packing Group:	N/A

Section 15 - Regulatory Information

Note: Materials listed in this section may be present as trace level contaminants to raw materials. Check Section 2 - Hazardous Ingredients to determine if a significant amount is present

OSHA: This product is considered hazardous under the Federal OSHA Hazard Communication Standard.

WHMIS: C, D2B,

SARA Title III:

Section 302 Extremely Hazardous Substances: None

Section 311 / 312 Hazard Categories: Immediate health, delayed health, fire hazard.

Section 313 Toxic Chemicals: Benzoyl peroxide

You may be required to submit this MSDS to state and local emergency response agencies (SERC & LEPC) and to your local fire department. Also, you may be affected by other sections of this law, depending on the chemicals and amounts that you inventory at your location. To learn more about your responsibilities, call the EPA Hotline (800) 535-0202

TSCA status: All components in this product are on the TSCA Inventory.

Canadian Domestic Substances List: The components of this product ARE listed on the Canadian Domestic Substances List.

Proposition 65: This product DOES NOT contain a chemical regulated under California Proposition 65.

Section 16 - Preparation Information

Prepared by Bondo Corporation
Information phone number: (404) 696-2730

Do not handle until the manufacturer's safety precautions have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all products with which they come in contact.

While Bondo Corporation believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Bondo Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification.

Any use of these data and information must be determined by the user to be in accordance with applicable federal, state or provincial and local laws and regulations.