

# SAFETY DATA SHEET

Creation Date 24-Feb-2010 Revision Date 24-Dec-2021 **Revision Number** 5

1. Identification

**Product Name** Reagent Alcohol

Cat No.: A962-200; A962-4; A962-44LC; A962-F1GAL; A962-P4; A962-RB200;

A962-S4; NC1432463; XXA962PD20LI;

Denatured Alcohol; Denatured Ethanol **Synonyms** 

**Recommended Use** Laboratory chemicals.

Food, drug, pesticide or biocidal product use. Uses advised against

### Details of the supplier of the safety data sheet

# Company

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** CHEMTREC®, Inside the USA: 800-424-9300

CHEMTREC®, Outside the USA: 001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2 Acute oral toxicity Category 4 Acute Inhalation Toxicity - Vapors Category 4 Serious Eye Damage/Eye Irritation Category 2 Specific target organ toxicity (single exposure) Category 1 Target Organs - Central nervous system (CNS), Optic nerve, Respiratory system.

Category 1

Specific target organ toxicity - (repeated exposure)

Target Organs - Kidney, Liver, spleen, Blood.

# Label Elements

# Signal Word

Danger

# **Hazard Statements**

Highly flammable liquid and vapor Harmful if swallowed Harmful if inhaled Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



# **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

# Response

IF exposed: Call a POISON CENTER or doctor/physician

# Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

# Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Lyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None identified

#### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

Revision Date 24-Dec-2021 Reagent Alcohol

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	90
Methyl alcohol	67-56-1	5.0
Isopropyl alcohol	67-63-0	5.0

### 4. First-aid measures

If symptoms persist, call a physician. **General Advice** 

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.

Do NOT induce vomiting. Call a physician or poison control center immediately. Ingestion

Most important symptoms and

effects

**Notes to Physician** 

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting: May cause blindness

Treat symptomatically

# 5. Fire-fighting measures

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

**Unsuitable Extinguishing Media** Water may be ineffective

12.8 - 14.4 °C / 55 - 57.9 °F **Flash Point** 

Method -No information available

362.8 °C / 685 °F **Autoignition Temperature** 

**Explosion Limits** 

Upper 19 vol % 3.3 vol % Lower

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). Thermal decomposition can lead to release of irritating gases and vapors. **Protective Equipment and Precautions for Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Physical hazards Health **Flammability** Instability N/A

Revision Date 24-Dec-2021 Reagent Alcohol

### Accidental release measures

**Personal Precautions** 

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** 

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Metals. Acid anhydrides. Acid chlorides.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm	STEL: 1000 ppm
		(Vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm	
		TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>	
		TWA: 1900 mg/m <sup>3</sup>		
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	
		Skin	STEL: 325 mg/m <sup>3</sup>	
		TWA: 200 ppm		
		TWA: 260 mg/m <sup>3</sup>		
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm	STEL: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m <sup>3</sup>	
		(Vacated) STEL: 1225	STEL: 500 ppm	
		mg/m³	STEL: 1225 mg/m <sup>3</sup>	
		TWA: 400 ppm		
		TWA: 980 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures** 

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

# Personal Protective Equipment

**Eye/face Protection** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

\_

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceClearOdorAlcohol-like

Odor Threshold No information available

pH No information available
Melting Point/Range -114.1 °C / -173.4 °F
Boiling Point/Range 78.5 °C / 173.3 °F

Flash Point 12.8 - 14.4 °C / 55 - 57.9 °F

Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper Lower
 19 vol %

 Lower
 3.3 vol %

 Vapor Pressure
 44 mmHg

 Vapor Density
 1.24

 Specific Gravity
 0.8

 Solubility
 miscible

Partition coefficient; n-octanol/water

Autoignition Temperature

No data available
362.8 °C / 685 °F

No information available
Viscosity

No information available

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases, Metals, Acid anhydrides, Acid

chlorides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to release

of irritating gases and vapors

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Oral LD50** Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Category 4. ATE = 10 - 20 mg/l.

**Component Information** 

Component LD50 Oral LD50 Dermal LC50 Inhalation

Revision Date 24-Dec-2021 Reagent Alcohol

Ethyl alcohol	LD50 = 10470 mg/kg	Not listed	LC50 = 117-125 mg/l (4h)
-	OCED 401 (Rat)		OECD 403 (rat)
	3450 mg/kg ( Mouse )		20000 ppm/10H (rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
	3600 mg/kg ( Mouse )	, ,	- ` '

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritating to eyes and respiratory system Irritation

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Ethanol has been shown to be carcinogenic in long-term studies only when consumed and

abused as an alcoholic beverage.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Not listed	Known	A3	Not listed	A3
Methyl alcohol	67-56-1	Not listed				
Isopropyl alcohol	67-63-0	Not listed				

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial

Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** Component substance is listed on California Proposition 65 as a developmental hazard.

No information available. **Teratogenicity** 

STOT - single exposure Central nervous system (CNS) Optic nerve Respiratory system

STOT - repeated exposure Kidney Liver spleen Blood

No information available **Aspiration hazard** 

NTP: (National Toxicity Program)

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting: May cause blindness

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800  mg/L/24h

		LC50 = 14200 mg/l/96h	mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Isopropyl alcohol	EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

**Persistence and Degradability** 

Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** 

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Isopropyl alcohol	0.05

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	•

# 14. Transport information

DOT

**UN-No** UN1987

Proper Shipping Name ALCOHOLS, N.O.S

Hazard Class 3 Packing Group II

TDG

**UN-No** UN1987

Proper Shipping Name ALCOHOLS, N.O.S

Hazard Class 3
Packing Group ||

**IATA** 

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S

Hazard Class 3
Packing Group ||

# 15. Regulatory information

# **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl alcohol	64-17-5	Χ	ACTIVE	-
Methyl alcohol	67-56-1	X	ACTIVE	-
Isopropyl alcohol	67-63-0	X	ACTIVE	-

### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

#### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl alcohol	64-17-5	Χ	-	200-578-6	Χ	Χ	Χ	Х	Х	KE-13217
Methyl alcohol	67-56-1	Χ	-	200-659-6	Х	Χ	Χ	Х	Х	KE-23193
Isopropyl alcohol	67-63-0	Х	-	200-661-7	Х	Χ	Х	Х	Х	KE-29363

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

# U.S. Federal Regulations

#### **SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	5.0	1.0
Isopropyl alcohol	67-63-0	5.0	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

**CERCLA** 

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Methyl alcohol	5000 lb	-	

### **California Proposition 65**

This product contains the following Proposition 65 chemicals. Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	Ethyl alcohol 64-17-5		-	Developmental
		beverages only)		Carcinogen
		Carcinogen		

Methyl alcohol	67-56-1	Developmental	-	Developmental

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X
Methyl alcohol	X	X	X	X	X
Isopropyl alcohol	X	X	X	-	X

**U.S. Department of Transportation** 

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	• • • • • • • • • • • • • • • • • • • •
Methyl alcohol	-	Use restricted. See item 69.	-
		(see link for restriction details)	
Isopropyl alcohol	-	Use restricted. See item 75.	-
·		(see link for restriction details)	

https://echa.europa.eu/substances-restricted-under-reach

# Safety, health and environmental regulations/legislation specific for the substance or mixture

	Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ī	Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable
	Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Ī	Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl alcohol	64-17-5	Not applicable	Not applicable	Not applicable	Annex I - Y42
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 24-Feb-2010

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

### **Revision Summary**

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**