

2/24/93

0-8605

MATERIAL SAFETY DATA SHEET

FOR PRINTING INK AND RELATED MATERIALS

INFORMATION ON THIS FORM IS PROPRIETARY INFORMATION AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS

DATE OF PREP. 7/15/85 PREPARED BY _____

HAZARD RATINGS

Minimal..... 0
Slight..... 1
Moderate..... 2
Serious..... 3
Severe..... 4

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

Section I

DISTRIBUTOR'S
 MANUFACTURER'S NAME: Van Son Holland Ink Corp.
 STREET ADDRESS: 92 Union Street CITY, STATE AND ZIP CODE: Mineola, NY 11501
 EMERGENCY TELEPHONE NUMBER: 516-294-8811
 PRODUCT CLASS: Hydrocarbon Solvent Gel
 TRADE NAME: Tack Reducer MANUFACTURER'S CODE IDENTIFICATION: _____

Section II - HAZARDOUS INGREDIENTS

Ingredient:	Hazard Data:
Petroleum Naphtha	CAS 8030-30-6

Section III - PHYSICAL DATA

BOILING RANGE °F 328-510	VAPOR DENSITY: HEAVIER <input checked="" type="checkbox"/> vs. air LIGHTER <input type="checkbox"/>	LIQUID DENSITY: HEAVIER <input type="checkbox"/> vs. water LIGHTER <input checked="" type="checkbox"/>	TYPE OF ODOR Solvent Odor
APPEARANCE Semi Opaque Gel	EVAPORATION RATE FASTER <input type="checkbox"/> vs. Butyl Acetate SLOWER <input checked="" type="checkbox"/>	PERCENT VOLATILE WT. 80%	

Section IV - FIRE & EXPLOSION DATA

FLAMMABILITY CLASSIFICATION Combustible	OSHA Class IIIA DOT	FLASH POINT °F 100 (Method Used) -200	LEL
--	------------------------	--	-----

EXTINGUISHING MEDIA:

FOAM "ALCOHOL" FOAM CO2 DRY CHEMICAL WATER FOG OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS Keep work areas free of hot metal surfaces

SPECIAL FIREFIGHTING PROCEDURES Self contain breathing apparatus recommended for fire fighters

