



AMERICAN INTERNATIONAL INDUSTRIES

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Gena Adios **Nail Polish Remover**

DATE: 6/25/2004

FORMULA: 30-8030

REV. NEW

Section 1. Material Identification and Information

Hazardous Ingredients:

| Component | CAS # | % | TOXICOLOGICAL DATA |
|-------------------------------|---------|-------|--|
| Acetone | 67-64-1 | 78.5% | OSHA PEL: 1000ppm ACGIH TVL: 760ppm |
| Isopropyl Alcohol, 2-Propanol | 67-63-0 | 1% | OSHA PEL: 400ppm ACGIH TVL: 400ppm |

Section 2. Physical / Chemical Characteristics

| | |
|---|--|
| Boiling Point: 133-180°F | Specific Gravity: 0.83 |
| Vapor Pressure: 0.19mmHg @ 68°F (mm Hg and Temperature) | (H ₂ O = 1) |
| Vapor Density: Heavier than Air | Density: 6.88lb/gl |
| Solubility in Water: Soluble | Evaporation Rate: Slower than Ether |
| Appearance: Pink Liquid | Material VOC: 8g/L |
| Odor: Mild Odor | |

Section 3. Fire and Explosion Hazard Data

| | |
|--|---|
| Flash Point and Method Used: | 1°F TOC |
| Auto-Ignition Temperature: | N/A |
| Flammability Limits in Air % by Volume: | LEL: 2% |
| | UEL: 12.8% |
| Extinguisher Media: | Alcohol foam, carbon dioxide, dry chemical, or water fog. |
| Special Fire Fighting Procedures: | EXTREMELY FLAMMABLE! Use NIOSH approved self-contained breathing apparatus. |
| Unusual Fire and Explosion Hazards: | Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture. |

Section 4. Reactivity Hazard Data

Stability: Stable Unstable

Conditions to Avoid: Avoid heat, sparks, and open flame.

Incompatibility (Materials to Avoid):
Strong oxidizing agents.

Hazardous Decomposition:
Thermal decomposition may yield carbon dioxide and/or carbon monoxide

Hazardous Polymerization:
 May Occur Will Not Occur

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Gena Adios Nail Polish Remover**DATE:** 6/25/2004**FORMULA:** 30-8030**REV.** NEW

Section 7. Precautions for Safe Handling and Use / Leak Procedures

Steps to be Taken if Material is Spilled or Released:

Remove all sources of ignition and provide ventilation. Large spills may be pumped to salvage vessels. Small spills may be picked up with an absorbent material.

Waste Disposal Methods:

Place in tightly closed containers and dispose of in accordance with local, state, and federal regulations.

Precautions to be taken in Handling and Storing:

Keep away from heat, sparks, and open flames. Keep containers closed when not in use. Use with adequate ventilation.

Other Precautions and/or Special Hazards:

Do not take internally. Ground equipment to prevent accumulation of static charge. Do not cut, weld, drill, or grind on or near containers.

Section 8. Regulatory Information

California Proposition 65:

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Benzene

This product contains a chemical known to the State of California to cause cancer.

Contains: Benzene (Trace)