



SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

Formaldehyde 37% M15%

Section 1. Product and company identification

GHS product identifier : Formaldehyde 37% M15%
NFPA Number : 000000100000
Product type : Formaldehyde Solution
Material use : Industrial use.

Manufacturer/Supplier/Importer : Hexion Inc.
100 East Broad Street
Columbus, Ohio
43215 USA

Contact person : 4information@hexion.com

Telephone : For additional health and safety or regulatory information, call
1 888 443 9466.

Emergency telephone number : For Emergency Medical Assistance
Call Health & Safety Information Services
1-866-383-6949

For Emergency Transportation Information
CHEMTREC US Domestic (800) 424-9300
CHEMTREC International (703) 527-3887
CANUTEC CA Domestic (615) 996-6666

Section 2. Hazards identification

Classification of the substance or mixture :
FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY:oral - Category 4
ACUTE TOXICITY:dermal - Category 3
ACUTE TOXICITY:inhalation - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
RESPIRATORY SENSITIZATION - Category 1
HEIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1B
TOXIC TO REPRODUCTION - Category 1B
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
[central nervous system (CNS)] - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) [respiratory tract, skin, kidneys, liver, gastrointestinal tract] - Category 2

GHS label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H326 Flammable liquid and vapor.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H312 Causes skin irritation.
H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H360F May damage fertility.
H360D May damage the unborn child.
H370 Causes damage to organs: (central nervous system (CNS))
H373 May cause damage to organs through prolonged or repeated exposure: (respiratory tract, skin, kidneys, liver, gastrointestinal tract)

Precautionary statements

General

Not applicable.

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Wear protective gloves.
Wear eye or face protection.
Wear protective clothing.
In case of inadequate ventilation wear respiratory protection.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Keep container tightly closed.
Use only outdoors or in a well-ventilated area.
Do not breathe vapor.
Do not eat, drink or smoke when using this product.
Wash hands thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.

Response

Get medical attention if you feel unwell.
IF EXPOSED:
Call a POISON CENTER or physician.
IF INHALED:
Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a **POISON CENTER** or physician.
 If experiencing respiratory symptoms:
 Call a **POISON CENTER** or physician.
IF SWALLOWED:
 Call a **POISON CENTER** or physician if you feel unwell.
 Rinse mouth.
IF ON SKIN (or hair):
 Take off immediately all contaminated clothing.
 Rinse skin with water or shower.
IF ON EYES:
 Wash with plenty of soap and water.
 Call a **POISON CENTER** or physician if you feel unwell.
 Take off contaminated clothing.
 If skin irritation or rash occurs:
 Get medical attention.
IF IN EYES:
 Rinse continuously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a **POISON CENTER** or physician.

Storage : Store locked up.
 Store in a well-ventilated place.
 Keep cool.

Dispose : Dispose of contents and container in accordance with all local,
 regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS number
Formaldehyde	10 - 20	50-00-0
Methanol	10 - 30	67-56-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.
 Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Get medical attention immediately. Call a poison center or physician.
 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first aid personnel** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO2, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides irritating and toxic fumes and gases aldehydes
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding area. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flames or any other ignition sources. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Follow US NFPA 30, "Flammable & Combustible Liquids Code," or other national, state and local codes on safe handling of flammable liquids. Train workers in the recognition and prevention of hazards associated with the storage, handling and transfer of flammable liquids in the plant. Store in an area designated for storage of flammable liquids (See NFPA 30, and OSHA 29 CFR 1910.106)

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Version: 4.0

Date of issue/Date of revision: 03/26/2013

Date of previous issue: 04/12/2013

<p>Formaldehyde</p>	<p>ACGIH TLV (2000-05-01) Ceiling 0.37 mg/m³ 0.3 ppm OSHA PEL (1993-06-30) Time Weighted Average (TWA) 0.75 ppm Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 2 ppm NIOSH REL (1994-04-01) Time Weighted Average (TWA) 0.016 ppm Ceiling 6.1 ppm</p>
<p>Methanol</p>	<p>ACGIH TLV (1994-09-01) Time Weighted Average (TWA) 260 mg/m³ 200 ppm Short Term Exposure Limit (STEL) 520 mg/m³ 400 ppm OSHA PEL (1993-06-30) Time Weighted Average (TWA) 260 mg/m³ 200 ppm NIOSH REL (1994-04-01) Time Weighted Average (TWA) 260 mg/m³ 200 ppm Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 333 mg/m³ 250 ppm</p>

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work

Version: 8.0

Date of issue/Date of revision: 03/26/2015

Date of previous issue: 04/12/2013

- Eye/face protection** : clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid
Color : Clear, colorless/colorless
- Odor** : Fungus
Odor threshold : Not available
- pH** : 3.0 - 4.5
- Melting point/ Freezing point** : See storage section
- Boiling point** : 100 °C (212.00 °F)
- Flash point** : Setflash Closed Cup: 60 °C (140.00 °F) (ASTM D 3828)

Version: 0.0 Date of issue/Date of revision: 03/26/2015 Date of previous issue: 04/12/2013

Burning time	:	Not available
Burning rate	:	Not available
Evaporation rate	:	1 ((n-Butyl acetate-1))
Flammability (solid, gas)	:	Not available
Lower and upper explosive (flammable) limits	:	Lower: 7 %(V) Upper: 70 %(V)
Vapor pressure	:	40 mm Hg @ 25 °C (77.00 °F)
Vapor density	:	1 (Air = 1)
Relative density	:	1.8750 - 1.8810
Solubility	:	Not available
Solubility in water	:	Infinite
Partition coefficient: n-octanol/water	:	Not available
Auto-ignition temperature	:	420 °C (788.00 °F)
Decomposition temperature	:	Not available
SAFT	:	Not available
Viscosity	:	Dynamic: Not available Kinematic: Not available

Other information

The SDS is not to be used as a specification sheet. For specific technical information on the product listed above, a sales specification sheet should be obtained from your Houston representative.

Section 10. Stability and reactivity

Reactivity	:	Stable under normal conditions.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressure, cut, weld, heat, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials strong acids, strong alkalis, phenol HYDROCHLORIC ACID
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde	LD50 Oral	Rat	500 mg/kg	-
	LC50 Inhalation	Rat	0.170 mg/l	2h
	LD50 Dermal	Rabbit	270 mg/kg	-
Methanol	LD50 Oral	Rat	3.620 mg/kg	-

Conclusion/Summary : Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Formaldehyde	Skin - Erythema/Echym	Rabbit	2.5	20 hrs	-
	Skin - Edema	Rabbit	3	20 hrs	-
	eyes - Cornea opacity	Mouse	> 3		-

Conclusion/Summary :
 Skin : Not available
 eyes : Not available
 Respiratory : Not available

Sensitization

Conclusion/Summary :
 Skin : Not available
 Respiratory : Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde	*****	-		
Remarks:	The National Toxicology Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA Formaldehyde Workplace Standard at 29 CFR 1926.1048 (the "OSHA Standard"). Safe handling and use instructions are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an			

	<p>eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov/SLPC/formaldehyde; http://monographs.iarc.fr; http://ntp-server.niehs.nih.gov; http://epa.gov/iris/subst/0419.htm; http://www.nap.edu/catalog.php?record_id=13142 and other authoritative websites.</p>
--	---

Conclusion/Summary : Not available

Respiratory toxicity

Conclusion/Summary : Not available

Toxicokinetics

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Formaldehyde	Category 3		Respiratory tract irritation
Methanol	Category 3 Category 1 Category 2		Respiratory tract irritation central nervous system (CNS) optic nerve

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Formaldehyde	Category 2		respiratory tract skin
Methanol	Category 2		kidneys liver gastrointestinal tract skin respiratory tract

Application hazard

Not available

Information on the likely routes of exposure : Not available

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : Toxic if inhaled. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. May cause allergy or asthma

- Skin contact** : symptoms or breathing difficulties if inhaled.
Toxic in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pain
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available
Potential delayed effects : Not available

Long term exposure

- Potential immediate effects** : Not available
Potential delayed effects : Not available

Potential chronic health effects

- Conclusion/Summary** : Not available
- General** : May cause damage to organs through prolonged or repeated exposure:
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
Teratogenicity : May damage the unborn child.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Formaldehyde	Acute LC50 6.7 mg/l	Fish - Striped bass	96 h
	Acute LC50 6.9 mg/l	Fish - Fathead minnow	6 d
	Acute NOEC > 47.9 mg/l	Fish - Medaka, Males, High-cym	28 d
	Acute EC50 3.8 mg/l Fresh water	Aquatic invertebrates - Water flea	3 d
	Acute EC50 4.9 mg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 4.3 mg/l Fresh water	Aquatic plants - Algae	48 h
	Acute EC50 19 mg/l	Micro-organisms - Soil organisms	3 h
Methanol	Acute EC50 13,000 mg/l Fresh water	Fish - Rainbow trout, brook trout	4 d

Conclusion/Summary : Not available

Persistence/biodegradability

Conclusion/Summary : Not available

Bioaccumulative potential

Product/ingredient name	LogPow	K _{OW}	Potential
Formaldehyde	0.33	< 1	low
Methanol	-0.77	-	low

Mobility in soil

Soil/water partition coefficient (K_{OC}) : Not available
 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local

authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residue. Vapor from product residue may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of according to all federal, state and local applicable regulations.

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory information	UNTA number	Proper shipping name	Classes*PG	Reportable Quantity (RQ)
CFR	1198	FORMALDEHYDE SOLUTION, FLAMMABLE	Class 3 (8) III	Formaldehyde, Methanol
TDG	1198	FORMALDEHYDE SOLUTION, FLAMMABLE	Class 3 (8) III	
IMO/IMDG	1198	FORMALDEHYDE SOLUTION, FLAMMABLE	Class 3 (8) III	Formaldehyde, Methanol
IATA (Cargo)	1198	FORMALDEHYDE SOLUTION, FLAMMABLE	Class 3 (8) III	Formaldehyde, Methanol

*PG : Packing group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

HCS Classification : Combustible liquid
 Toxic material
 Corrosive material
 Sensitizing material
 Carcinogen
 Target organ effects

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None required.
 United States - TSCA 2(a)(3) - Final significant new use rules: Not listed
 United States - TSCA 2(a)(3) - Proposed significant new use rules: Not listed
 United States - TSCA 3(a) - Substances consent order: Not listed

SARA 313

	Product name	CAS number
Form R - Reporting requirements	Formaldehyde	50-00-0
	Methanol	67-56-1
Inventory notification	Formaldehyde	50-00-0
	Methanol	67-56-1

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

California Prop. 65 : **WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Formaldehyde	Yes	No	49 mg/day	No
Methanol	No	Yes	No	No

United States Inventory (TSCA 9a) : All components are listed or exempted.

Canada

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
 Class D-1A: Material causing immediate and serious toxic effects (Very toxic).
 Class D-2A: Material causing other toxic effects (Very toxic).
 Class D-2B: Material causing other toxic effects (Toxic).
 Class E: Corrosive material

Canadian Lists

Canadian NPRI : The following components are listed: Formaldehyde Methanol

CEPA Toxic substances : The following components are listed: Formaldehyde

Version: 4.0

Date of issue/Date of revision: 03/26/2015

Date of previous issue: 04/12/2011

International regulations

International lists : Australia Inventory (AICE): All components are listed or exempted.
 Canada Inventory: All components are listed or exempted.
 Japan Inventory: All components are listed or exempted.
 China Inventory (IECBC): All components are listed or exempted.
 Korea Inventory: All components are listed or exempted.
 New Zealand Inventory (NZIEIC): All components are listed or exempted.
 Philippines Inventory (PIEC): All components are listed or exempted.
 United States Inventory (FDCA 90): All components are listed or exempted.
 Taiwan Inventory (CEIC): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (H.M.I.S.) :

Health	3
	3
	3

Caution: HMISO ratings are based on a 6-4 rating scale, with 6 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMISO ratings are not required on MSDSs under 19 CFR 1418.1208, the preparer may choose to provide them. HMISO ratings are to be used with a fully implemented HMISO program. HMISO is a registered mark of the National Paint & Coatings Association (NPCA). HMISO materials may be purchased exclusively from J. J. Keller (800) 337-6000. The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H statements : Not applicable.

History

Date of printing : 06/03/2013
Date of issue/Date of revision : 03/26/2013
Date of previous issue : 04/12/2013
Version : 1.0
Prepared by : Product Safety Stewardship
Key to abbreviations : ATE - Acute Toxicity Estimate
 BCE - Bioaccumulation Factor
 GHS - Globally Harmonized System of Classification and Labeling of Chemicals
 IATA - International Air Transport Association
 IBC - Intermediate Bulk Container
 IMDG - International Maritime Dangerous Goods
 LogPow - logarithm of the octanol/water partition coefficient
 MARPOL 73/78 - International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" - marine pollution)
 REG - The Regulations concerning the International Carriage of Dangerous Goods by Rail
 UN - United Nations
References : Not available

Notice to reader

Version: 1.0 **Date of issue/Date of revision:** 03/26/2013 **Date of previous issue:** 04/12/2013

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. **HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION,** except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

© and (TM) Licensed trademarks of Hexion Inc.